

MOUNTING BLOCK COVER

| | |
|--------------------|---|
| Material | : Polycarbonate |
| IP Rating | : IP66 on all models |
| Rated Frequency | : 50/60Hz |
| Max. Cable Size | : 16mm ² |
| Inclusions | : Fix neutral and earth bars |
| Features | : Lockable - suggested padlock 6mm or less Screwed entries - 4 x 25mm Cutouts - 2 x 25mm Comes with rubber o-rings |
| Compliance | : AS 60947.3:2018 AS/NZS IEC 60947.1:2015 |
| Product Dimensions | : 172 L x 83 W x 72 D |
| Package Dimensions | : 175 L x 85 W x 92 D |



**All dimensions in millimetres unless specified*

| Part Number | Pole | Amps | Voltage | M Rating |
|-------------|------|------|---------|----------|
| WPIS 120 | 1 | 20 | 250V AC | M140 |
| WPIS 135 | 1 | 35 | 250V AC | M180 |
| WPIS 220 | 2 | 20 | 440V AC | M140 |
| WPIS 235 | 2 | 35 | 440V AC | M180 |
| WPIS 320 | 3 | 20 | 440V AC | M100 |
| WPIS 335 | 3 | 35 | 440V AC | M140 |
| WPIS 363 | 3 | 63 | 440V AC | M200 |

Warranty

5 Year Limited

