

LED 40 WATT BATTEN LIGHT

Material	: PC milky diffuser PC base
Lead Length	: 1.4M
Watt	: 40 watt maintained
Driver	: Non-isolated
Driver Efficiency	: >90%
Battery	: Li-ion 2W-3H
IP Rating	: IP65
Impact Rating	: IK10
Colour Temperature	: 4000k
Input Voltage	: 220-240V
Frequency	: 50/60Hz
Ambient Temperature	: -20°C to 40°C
LED Type	: SMD2835
Beam Angle	: 120
Lifetime Hours	: 50,000
PF	: >0.9
CRI	: 80
IRF	: 5%
THD	: <15%
Lumen	: 130 LM
Glow Wire Test	: 650°C
Installation	: Surface mounting
Features	: Plug and lead included Steel gear tray Rear cable entry Quick-screw end cap
Compliance	: CE, RoHS
AS Classification	: AS 60598.2.22:2019, AS 2293 (C ⁰ = D50, C ⁹⁰ = D25)
Product Dimensions	: 1165 x 76 x 72
Package Dimensions	: 1170 L x 80 W x 75 H



*All dimensions in millimetres unless specified

Limited Warranty

Case	12,000 hours
Battery	3 years
LED	12,000 hours
Driver	5 years

Emergency Specifications:

LED light complete with plug and lead

Emergency Watt	: 2W
Duration	: ≥ 3 hours
Chargers	: ≥ 25 hours
Battery	: LifePO4-6.4V 3000mAH
Output	: 10-42V/100mA